


# Usertifisert jernvare

## Industrial hardware

### Kortlenket kjetting, rustfritt syrefast stål AISI 316 - DIN 766


Short link chain, stainless steel AISI 316 - DIN 766



Artikkelnummer	Diameter mm	Ca. bruddstyrke kg	Innvendig bredde mm	Innvendig lengde mm	Vekt kg/m
0230102	2	125	3,5	12,0	0,07
0230103	3	280	5,0	16,0	0,17
0230104	4	630	6,0	16,0	0,32
0230105	5	1 000	6,0	18,5	0,50
0230106	6	1 250	7,2	18,5	0,80
0230108	8	2 500	9,6	24,0	1,40
0230110	10	4 000	12,0	28,0	2,30
0230113	13	6 300	15,6	36,0	3,80

### Langlenket kjetting, rustfritt syrefast stål AISI 316 - DIN 763


Long link chain, stainless steel AISI 316 - DIN 763



Artikkelnummer	Diameter mm	Ca. bruddstyrke kg	Innvendig bredde mm	Innvendig lengde mm	Vekt kg/m
0230202	2	125	4	22	0,06
0230203	3	280	6	26	0,15
0230204	4	630	8	32	0,27
0230205	5	1 000	10	35	0,43
0230206	6	1 250	12	42	0,63
0230208	8	2 500	16	52	1,10

### Skjøtelenke for kjetting, galvanisert

Connecting link for chain, galvanized



Artikkelnummer	Diameter (d) mm	b mm	h mm	m mm	Vekt kg/100stk
0351803	3	6,5	16,5	4,0	0,4
0351804	4	8,0	20,0	5,5	0,8
0351805	5	9,5	23,0	6,0	1,2
0351806	6	10,5	29,0	7,0	2,1
0351808	8	15,0	37,0	9,0	5,6
0351810	10	17,0	37,5	9,0	9,5